# DTK-SL Series

66 Block Surge Protectors




**DITEK's DTK-SL Series** quick–connect surge protectors are designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage.

## PRODUCT FEATURES

- Quick connect module – no bridge clips required
- Each Snap-It protects one pair
- LED diagnostic indicator
- Small form factor reduces installation space requirements
- Requires (1) DTK-SIGB ground bar per 66 block

## APPLICATIONS

- 25V Intercom Speakers
- Analog Phone Systems

## ACCESSORIES

- DTK-SIGB

| TECHNICAL SPECIFICATIONS | | |
|---|---|---|
| **DTK-SL** | **30B** | **130B** |
| Service Voltage: | 30Vdc | 130Vdc |
| MCOV: | 48V | 150V |
| Clamping Voltage: | 59V | 167V |
| Wiring Configuration: | 1 pair | |
| Protection Modes: | Differential Mode (Line-Line)<br>Common Mode (Line-Ground) | |
| Surge Current Rating: | 5,000A | |
| Max. Continuous Current: | 2 amps | |

**DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345**
**Diteksurgeprotection.com • SPS-100055-001 Rev 8 05/26**

LISTED

MADE IN USA

Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

# DTK-SL Series

66 Block Surge Protectors

| MECHANICAL SPECIFICATIONS | |
|---|---|
| Connection Method: | 66 block snap-on |
| Housing: | ABS |
| Operating Temperature: | -40°F – 158°F (-40°C – 70°C) |
| Maximum Humidity: | 95% non-condensing |
| Dimensions: | 3.24 in. L x 0.38 in. W x 1.56 in. H<br>(82 mm x 10 mm x 40 mm) |
| Weight: | 0.5 oz (14g) |

| SAFETY STANDARDS AND CERTIFICATIONS | |
|---|---|
| Certifications: | UL 497B |
| Standards Compliance: | RoHS |
| Warranty: | 10 Year Limited Warranty |



Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.